

Architectural LED Down light

Features:

- Industry Leading LED diodes
- High Performance Drivers
- 5-year warranty
- 40000 Hour Life
- TM-21, LM-79, LM-80, ISTMT (6000 hour test)
- Mercury Free
- Operate in Low Temperatures



Model	Description	Watts	Lumens	Equivalent	Beam Angle	CCT	CRI	Size	Life Span	Dimmable	Voltage	Energy Star	
AGL-AR-CDL6-22-30K-D	6" 22 Watt DL	22	1600	2x18W CFL	90°	3000K	80	6"	50000	Yes	120-277V	Yes	
AGL-AR-CDL6-22-35K-D	6" 22 Watt DL	22	1650	2x18W CFL	90°	3500K	80	6"	50000	Yes	120-277V	Yes	
AGL-AR-CDL6-22-40K-D	6" 22 Watt DL	22	1700	2x18W CFL	90°	4000K	80	6"	50000	Yes	120-277V	Yes	
AGL-AR-CDL8-32-30K-D	8" 32 Watt DL	32	2150	2x26W CFL	90°	3000K	80	8"	50000	Yes	120-277V	Yes	
AGL-AR-CDL8-32-35K-D	8" 32 Watt DL	32	2300	2x26W CFL	90°	3500K	80	8"	50000	Yes	120-277V	Yes	
AGL-AR-CDL8-32-40K-D	8" 32 Watt DL	32	2450	2x26W CFL	90°	4000K	80	8"	50000	Yes	120-277V	Yes	
AGL-AR-CDL9.5-48-30K-D	9.5" 48 Watt DL	48	3200	2x42W CFL	90°	3000K	80	9.5"	50000	Yes	120-277V	Yes	
AGL-AR-CDL9.5-48-35K-D	9.5" 48 Watt DL	48	3400	2x42W CFL	90°	3500K	80	9.5"	50000	Yes	120-277V	Yes	
AGL-AR-CDL9.5-48-40K-D	9.5" 48 Watt DL	48	3600	2x42W CFL	90°	4000K	80	9.5"	50000	Yes	120-277V	Yes	
10W Emergency Driver	AGL-AR-EMD-10W	To order this option add -EM after the model number											