

Industrial High Bay LED



Features:

- Industry Leading LED diodes
- High Performance SR Drivers
- 10-Year Warranty
- Copper core heat dissipation technology
- Third party ITL/DLC certified lab data
- TM-21, LM-79, LM-80, ISTMT (6000 hour test)
- 120 - 277 input voltage options
- Multiple Lens and Diffuser Options
- Light weight design
- No fans / No filters / No maintenance
- Wet location IP 65 Rated
- High Capacity Surge Suppression



Model	Description	Watts	Lumens	LPW	Equivalent	Beam Angle	Available CCT	CRI	Life Span	Dimmable	Voltage	DLC
AGL-AR-LB-60-xxK	60W Low Ba	60	7800	130	150W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes
AGL-AR-HB-100-xxK	100W High Bay	100	13000	130	250W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes
AGL-AR-HB-150-xxK	150W High Bay	150	19500	130	400W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes
AGL-AR-HB-200-xxK	200W High Bay	200	26000	130	400W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes
AGL-AR-HB-310-xxK	310W High Bay	310	45500	130	1000W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes
AGL-AR-HB-360-xxK	360W High Bay	360	52000	130	1000W HID	120°	4000K/5000K	85	100000	0-10V	120-277V	Yes